

ARCHITECTURAL STANDARDS

FLOOR FINISHES

PRODUCT DATA SHEET M50 FLOOR FINISHES

M50/130

PREFFERED SUPPLIER INFORMATION

NBS REFERENCE M50/15/25/130/170

MANUFACTURER:

GRADUS Ltd

Address Park Green, Macclesfield,

Cheshire, SK11 7LZ

Tel 01625 428922


E-mail <u>sales@gradusworld.com</u>

Website: http://www.gradusworld.com

Supplier: Contact: Amanda Tate, Business

Development Manager

amanda.tate@gradusworld.com



PRODUCT DESCRIPTION

ICL APPROVED SPECIFICATION

Range: Wall Street and Wall Street Stripe Tile

Type: Tufted Loop Pile Tile

Description: Wall Street features an attractive plain textured design in loop pile construction,

made with 100% regenerated nylon, ECONYL. Wall Street can be used alone or co-ordinate with Wall Street Stripes to create interesting and unique floor

schemes.

Application: Suitable for a wide variety of environments including commercial, education and

healthcare.

Other:

Environmental: Achieves BREEAM A+ (Constructed from 100% regenerated nylon)

Recyclable: Yes

Warranty: 10 year warranty, 10 year anti-static warranty

Production: Made in the UK

TYPICAL NBS SPECIFICATION

M50/130 RUBBER/PLASTICS/CORK/LINO/CARPET TILING

Standard: Carpet tiling to Imperial College London Architectural Standards

Location: See architects drawings and finishes schedules

Base: See architects drawings and finishes schedules. Refer to Gradus Technical Services

01625 428922

Preparation: BS 5325:2001 - Code of practice for installation of textile floor coverings

Carpet tiles:

Manufacturer: Gradus Ltd, Park Green, Macclesfield, Cheshire, SK11 7LZ (01625 428922)

Product reference: Wall Street/Wall Street Stripe Tile

Size: 500mm x 500mm

Type: Tufted Loop Pile Tile

Colour/Pattern: Yorkville, Brookdale, Broadway, Midtown, Bowery, Hamilton, Harlem, Hudson, Waterside,

Lincoln, Bronx, Riverdale / Tribecca, Ansonia, Gramercy, Nolta

BS EN Classification: BSEN 1307, BSEN 985 Test A, BSEN 13501-1



ARCHITECTURAL STANDARDS FLOOR FINISHES

PRODUCT DATA SHEET

M50 FLOOR FINISHES M50/130

Category: Wide range of environments including commercial, education and healthcare

Level of use Class: Class 4

Method of laying: Recommended adhesive, F.Ball & Co 01538 361633. Product F41. All carpet should be

laid in accordance with BS5325:2001 installation of textile floor covering.

Setting out: All carpets should be laid in accordance with BS5325:2001 installation of flexible

floorcovering. For further installation advice please contact Gradus Technical Services

01625 428922

Accessories: Edging strips at thresholds

Special requirements:

Carpet backing: Synthetic Non-Woven