

#### PREFERRED SUPPLIER INFORMATION

NBS REFERENCE M50

MANUFACTURER:

**MILLIKEN CONTRACT**

Beach Hill Plant, Gidlow Lane, Wigan

Lancashire

WN6 8RN

Tel: +44 (0)1942 826073 Fax: +44 (0)1942 826570

Website: [www.miliken地毯europe.com](http://www.miliken地毯europe.com)

Supplier Contact: Matt Tombs [Matt.tombs@milliken.com](mailto:Matt.tombs@milliken.com)



#### PRODUCT DESCRIPTION

##### ICL APPROVED SPECIFICATION

Range:	Omni
Styles:	Myriad/ Comfortable Concrete
Application:	Heavy contract use. Non directional design and thicker backing for enhanced acoustic performance.
Construction:	Tufted, Performance Loop Pile
Total Thickness:	10.2 mm
Tile Size:	457.2 x 457.2 mm
Standard Backing:	Comfort Plus <sup>2</sup> - 85% Recycled content Polyurethane cushion. Available with TractionBack <sup>®</sup> on request.
Face Fibre:	Invista Antron <sup>®</sup> Type 6,6 Nylon
Environmental:	85% Recycled content cushion backing, 14% Recycled content by total product weight, Manufactured using electricity from renewable sources. Carbon Neutral certification. GUT & CRI Green Label Plus certified for indoor air quality, BRE Certification.
Recycling:	85% recycled content Polyurethane backing. 14% recycled content by total product weight
Guarantees:	15 year wear guarantee, Lifetime Antistatic guarantee, Latent Defects guarantee.
Production:	Made in the UK



#### TYPICAL NBS SPECIFICATION

M50/130	<b>CARPET TILING</b>
Standard:	Carpet tiling to Imperial College London Architectural Standards.
Location:	See architects drawings and finishes schedules.
Base:	Raised access floor or cement screed as architects drawings.
Preparation:	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards. - Fabricated Underlay: N/A. Carpet tiles to be adhered direct to the subfloor. As clauses 410/420/430/440 and 460.
Carpet Tiles:	
Manufacturer:	Milliken Contract, Beach Hill Plant, Gidlow Lane, Wigan Lancashire WN6 8RN
Product reference	<b>Myriad/ Comfortable Concrete</b>
Size:	457.2 x 457.2 mm
Type:	Tufted, Performance Loop Pile
Colour,/pattern:	To architects finishes schedules.
BS EN 1307 Classification;	
Category:	General Contract
Level of use Class:	Class 3, Heavy Use.
Method of laying:	Fully bond with release adhesive as recommended by manufacturer.
Setting out:	As clause 610.
Accessories:	Edging strip at thresholds
Special requirements:	Carpet tiles to be set out so that joints do not fall on raised floor tile joints.
Carpet backing:	to be recyclable.